

Applicants: Lionel Vedrine
Serial No.: 10/520,981
Filing Date: August 29, 2005
Docket No.: P-5753 (102-627 PCT/US RCE)
Page 4

AMENDMENTS TO THE CLAIMS:

This listing of claims will replace all prior versions, and listings, of claims in the application.

1. (Currently Amended) A device for injecting a product, particularly for medical use, which comprises:

a body housing a hollow injection needle and a container containing the injectable product; the needle is connected to the body but able to move relative to the latter between an injection position and a retracted position;

a plunger that slides in the body and is displaceable relative to the latter to perform the injection; said container is closed at one end and is connected to this plunger but is able to move relative to the latter between a position that enables the injection to be performed and a retracted position;

means for holding the needle in position, which means normally holds the needle in the injection position and can be released to free the needle to move to said retracted position;

means for holding the container ~~in position~~, which means ~~normally~~ holds the container in the position that enables the injection to be performed, and can be released to free the container to move to said retracted position;

a piston engaged in the container and so shaped to have a blind hole located adjacent a peripheral portion ~~that, wherein,~~ in a first configuration of the piston or relative position of this piston and of this container, it closes the container in such a way as to isolate the product from the environment outside this container and, in a second configuration of the piston or relative position of this piston and of this container, said peripheral portion of said piston is deflected into said blind hole so as to allow ~~it allows~~ the product to pass between said piston and said container and out of the container without said piston being pierced, wherein the piston is spaced from, and not in contiguous contact with, the needle with the piston being in the second configuration or position, and

respective means for operating said means of holding the needle in position and said means of holding the container ~~in position~~, which, at the end of the injection, release the means of holding the needle in position before, or at the same time as, the means of holding the container ~~in position~~ are released.

2. – 4. (Cancelled)

5. (Previously Presented) The injection device as claimed in claim 1, which comprises spring means for moving the needle and the container to the retracted position without voluntary external action.

Applicants: Lionel Vedrine
Serial No.: 10/520,981
Filing Date: August 29, 2005
Docket No.: P-5753 (102-627 PCT/US RCE)
Page 6

6. (Currently Amended) The injection device as claimed in claim 1, in which said body forms a distal end wall perpendicular to the axis of the needle, wherein the needle projects, in the injection position, from said distal end wall to a distance equal to the desired depth of insertion of this needle during the injection.

7. (Previously Presented) The injection device as claimed in one of claims 1-6, in which said means for holding the needle in position comprise:

a needle-supporting part comprising at least one locking means; and

at least one tab that comprises a locking means able to engage with that of said needle-supporting part, this tab being moveable radially between a normal, radially inward position, in which said locking means engage with each other to keep said needle-supporting part in position relative to said body, and a radially outward position, in which a zone of the plunger moves this tab radially out to unlock it, thereby freeing said needle-supporting part from said body.

8. (Currently Amended) The injection device as claimed in one of claims 1-6, in which said means for holding the container ~~in position~~ comprise:

a flange formed at the opposite end of the container from the closed end of this container;

Applicants: Lionel Vedrine
Serial No.: 10/520,981
Filing Date: August 29, 2005
Docket No.: P-5753 (102-627 PCT/US RCE)
Page 7

~~engagement means integral with said plunger for connecting said flange to the~~
~~plunger;~~ and

at least one tab ~~comprising said engagement means and~~ able to move in the radial direction of ~~this~~ the plunger between a radially inward position, in which ~~said engagement means connect~~ said flange is connected to the plunger, and a radially outward position, in which said ~~engagement means are~~ tab is withdrawn radially wide of this flange, thereby releasing it.